

CITIZEN

Micro HumanTech

High performance with easy access
Ingenuously designed for easy operation and reliability



CITIZEN CL-S700

LABEL & BARCODE

Typical Applications

- Logistics
- Courier
- Shelf-Edge
- Retail
- Warehousing
- Textile
- Card Tags

Space-Saving Design Concept



The Hi-Open™ case lifts up vertically meaning that the printer's footprint does not change as the cover is opened making it ideal for tight spaces.

Front Loading Rewinder



The clever and unique CL-S700R includes an internal rewinder that is simplicity itself to use. The front door drops down and the liner or labels are loaded.

Easy Configuration



The large graphic LCD gives a clear indication of printer status and easy printer configuration.

CITIZEN

Micro HumanTech

Product Versions

Internal Peel & Rewind

The CL-S700R features an integrated peeler with liner rewinder for easy label dispensing. The peel sensor waits for each label to be taken before printing another.



300 dpi Resolution

The CL-S703 is ideal for small labels with 2D matrix barcodes such as Datamatrix, DataBar, QR-Code and PDF417 or printing company logos and idents and CE or WEEE logos.



Printer Specifications

| Model Version | CL-S700DT | CL-S700 | CL-S700R | CL-S703 | CL-S703R* |
|-----------------------------------|---|--|-----------------|---------------------------------------|-----------------|
| Technology | Direct Thermal | Thermal Transfer & Direct Thermal | | | |
| Resolution | 203 dpi (8 dots per mm) | | | 300 dpi (12 dots per mm) | |
| Print Speed (maximum) | 7 ips, 175mm/sec | 10 inches per second (254 mm / second) | | 8 inches per second (200 mm / second) | |
| Print Width (maximum) | 4.10 inches, 104.1 mm | | | | |
| Media Width (min to max) | 1.00 inches to 4.65 inches (25.4 mm to 118.1 mm) | | | | |
| Media Length (min to max) | 0.25 inches to 32.0 inches (6.35 mm to 812.8 mm) | | | | |
| Roll Size (max), Core Size (min) | 8 inches (200 mm) outside diameter. Core size minimum of 1 inch (25mm). External media slot | | | | |
| Media Sensor | Fixed front sensor | Fully adjustable rear sensor and high resolution front sensor | | | |
| Media Thickness (min to max) | 0.0025 inches - 0.01 inches (0.0635 - 0.254 mm) | | | | |
| Ribbon Size | | 3.40 inches (86.5 mm) maximum Outside Diameter. 1476 ft (450 metres) length. | | | |
| Ribbon Winding & Type | Direct thermal only | Ink side in or out, automatically sensing. Wax, Wax/Resin or Resin Type | | | |
| Ribbon System | | ARCP™ automatic ribbon tension adjustment | | | |
| Emulations (Languages) | Cross-Emulation™ - automatic switching between Zebra® ZPL-II® and Datamax® I-Class®, DMX400® | | | | |
| Standard Interfaces | Serial & USB | Parallel (IEEE-1284), Serial (RS-232C), USB (version 1.1) | | | |
| Optional Interfaces | Parallel, LAN, WLAN | Ethernet LAN (10/100 BaseT), Wireless LAN (802.11b, g, n*) | | | |
| Case Type, Mechanism Type | Hi-Open™ metal case with safe, soft-close feature. Hi-Lift™ mechanism with 90° opening | | | | |
| Control Panel | 4-line back-lit graphic LCD and 4 buttons | | | | |
| RAM (Standard Memory) | 16.0 Mb total, 1.0 Mb available for user | | | | |
| Flash (Non-Volatile Memory) | 4.0 Mb total, 1.0 Mb available for user | | | | |
| Windows® drivers, design software | Free-of-charge on CD with printer, including support for Windows® XP®, 2003, 2008, Vista® | | | | |
| Internal Peeler & Rewinder | No | No | Yes | No | Yes |
| Size (W x D x H mm) | 255 x 490 x 265 | 255 x 490 x 265 | 255 x 490 x 385 | 255 x 490 x 265 | 255 x 490 x 385 |
| Weight (approximately) | 12.5 Kg | 13.3 Kg | 17.6 Kg | 13.3 Kg | 17.6 Kg |
| Warranty | 2 Year Manufacturer's Warranty or 100 Km on printer. Printhead: 50 Kms or 6 months in TT mode | | | | |

CITIZEN CL-S700

LABEL & BARCODE

Features

- Hi-Lift™ mechanism for easy ribbon and media loading.
- Hi-Open™ case for vertical opening, no increase in footprint and safe closing.
- Cross-Emulation™: Zebra® and Datamax® languages standard and automatically selected.
- Backlit LCD control panel for easy configuration.
- Front access for all operations including media and ribbon changing.
- Power switch located in recess at front of printer.
- Adjustable media sensor as standard with label gap and black mark sensing.
- Ingenious front-loading rewriter for peeling or batch mode.
- Optional Wireless LAN and Ethernet, cutters and peelers

Dealer Stamp

1200000

CITIZEN

Micro HumanTech

Optional Media Handling

Two Autocutter Versions

The CL-S700 and CL-S703 printers feature two cutter types: a *heavy-duty* cutter for thick card and plastics media and a *high-speed* cutter for standard labels and paper.



Optional Peeler

An optional peeler can be added to the CL-S700 and CL-S703 giving the peel-and-present function without the height of the full liner rewriter case.



Batch Mode Printing

The CL-S700R can be used for 'core-to-core' batch label printing using the optional rewriter paper guide and paper core holder.



Auto Cutter Specifications

| Model | CL-S700DT, CL-S700, CL-S703 (Cutter does not fit on "R" models) | |
|--|---|---|
| Version | High Speed | Heavy Duty |
| Type | Running Blade | Rotary |
| Media Thickness | 0.0024 - 0.01 inches 0.06 - 0.25 mm | |
| Cut Length | Minimum: 1.00 inch, 25.4 mm Maximum: determined by software | |
| Speed: time/cut | 0.3 seconds | 0.8 seconds |
| Cuts/thickness 0.06-0.15mm 0.15-0.25mm | 300,000 cuts 100,000 cuts | 500,000 cuts 200,000 cuts |
| Suggested Media Types | Card or ticket media, adhesive labels on backing | Textile, PET, thin plastic, thick card or tickets |
| Media Guidelines | Fanfold or Roll media. Roll media should be on a minimum 50mm core. Cut quantity may not be guaranteed with adhesives | |
| Cut tolerance | ± 1 mm horizontal and vertical | |
| Weight (approx.) | 0.46 Kg | 0.80 Kg |

Peeler Specifications

| Model | CL-S700DT, CL-S700, CL-S703 | CL-S700R CL-S703R* |
|---|--|--------------------------------------|
| Installation | Optional | Standard |
| Liner rewinding | No | Integral front-loading spool |
| Label-taken sensor | Standard | Standard |
| Type | S-bend, silicone dual roller | |
| Liner Thickness | 0.07mm, 0.0027 inches (max) | |
| Label Thickness | 0.17mm, 0.0067 inches (max) | |
| Liner Width | 25 - 118mm, 1 - 4.65 inches | |
| Label Length (min) | 1 inch, 25.4mm | |
| Label Length (max) Table Top Table Edge | 120mm, 4.72 inch 812mm, 32.0 inch | 280mm, 11.0 inch 812mm, 32.0 inch |
| Print Speed | Not to exceed 7 inches per second | |
| Label width | To be narrower than liner | |
| Number of Labels | 100 Km or 1 million peeled labels (when using specified media) | |

CITIZEN CL-S700

LABEL & BARCODE

General Applications

- Logistics and Courier Labels



- Warehouse and Distribution



- Retail and Item Labelling

