

KC Counting Indicator

General Specifications

- | | |
|--------------------------------|---|
| • Display | 20mm digit LCD display, with white LED backlight |
| • Keyboard | 20keys(Membrane keyboard) |
| • Housing | ABS plastic |
| • Max. Divisions | 30,000d |
| • Load cell excitation voltage | 5V/150mA |
| • ADC update | ≤1/10 second |
| • Operate Temp | 0°C~+40°C |
| • Power | AC adapter (12V/500mA), rechargeable battery (6V/4Ah) |
| • Gross weight | 2.6kg |



- Responds quickly with accurate weights
- Application: 1. Piece counting 2. Preset tare 3. Piece checking alarm
4. Accumulation 5. Weighing units conversion
6.10 unit weigh memory function
- Battery provide up to 70 hours of continuous use (without backlight)
- Optional RS-232 communication interface, connect PC or printer






KC Counting Indicator

Model Name	Capacity	Readability	Division	Approx. weight	Approval
KC	X	X	30,000d	2.6kg	CE

Options



Dimensions(mm)



Print formats

```

2012/03/01   15:10:12
S/N0:        2
WEIGHT:      10.762kg
UNIT.WT:     86.0990 g
COUNT:      125pcs
    
```

```

2012/03/01   15:10:22
S/N0:        2
TOTAL WT:    21.524kg
TOTAL.PCS:   250pcs
    
```