

NB/NHB Precision Balance

General Specifications

- Display 16.5mm digit LCD display, with white LED backlight
- Capacities 150g~6000g
- Pan size $\Phi 80\text{mm}$, $\Phi 120\text{mm}$, $140\text{mm} \times 150\text{mm}$
- Keyboard 7 keys (Membrane keyboard)
- Housing ABS plastic
- Max. Divisions 6,000e/30,000d/60,000d/150,000d/200,000d
- ADC update $\leq 1/10$ second
- Operating Temp. $+5^{\circ}\text{C} \sim +40^{\circ}\text{C}$
- Power AC adapter (12V/500mA), Rechargeable battery (6V/1.2Ah)
- Gross weight 2.9kg (with wind shield), 2.7kg (without wind shield)




- Standard RS-232 interface
- OIML approval from DELTA (approval no.DK0199.266)
- Rechargeable battery provides up to 40 hours of continuous use (without backlight)
- Optional below bench weighing
- Optional USB communication port
- Optional rear display
- Optional bluetooth (4.3GHz, 10m)
- Applications: 1. Percentage weighing 2. Counting 3. Accumulation
- 4. Weighing unit conversion



NB/NHB Precision Balance

| Model Name | Capacity | Readability | Division | Pan Size | Approx. weight | Approval |
|------------|----------|-------------|----------|-------------|----------------|----------|
| NB-300 | 300g | 0.01g | 30,000d | Φ 120mm | 2.9kg | CE |
| NB-600 | 600g | 0.02g | 30,000d | Φ 120mm | 2.9kg | CE |
| NB-1500 | 1500g | 0.05g | 30,000d | 140 x 150mm | 2.7kg | CE |
| NB-3000 | 3000g | 0.1 | 30,000d | 140 x 150mm | 2.7kg | CE |
| NB-6000 | 6000g | 0.2g | 30,000d | 140 x 150mm | 2.7kg | CE |
| NHB-300 | 300g | 0.005g | 60,000d | Φ 120mm | 2.9kg | CE |
| NHB-600 | 600g | 0.01g | 60,000d | Φ 120mm | 2.9kg | CE |
| NHB-1500 | 1500g | 0.02g | 60,000d | 140 x 150mm | 2.7kg | CE |
| NHB-3000 | 3000g | 0.05g | 60,000d | 140 x 150mm | 2.7kg | CE |
| NHB-6000 | 6000g | 0.1g | 60,000d | 140 x 150mm | 2.7kg | CE |
| NB-300M | 300g | 0.05g | 6,000e | Φ 120mm | 2.9kg | CE, OIML |
| NB-600M | 600g | 0.1g | 6,000e | Φ 120mm | 2.9kg | CE, OIML |
| NB-1500M | 1500g | 0.2g | 6,000e | 140 x 150mm | 2.7kg | CE, OIML |
| NB-3000M | 3000g | 0.5g | 6,000e | 140 x 150mm | 2.7kg | CE, OIML |
| NB-6000M | 6000g | 1g | 6,000e | 140 x 150mm | 2.7kg | CE, OIML |
| NHB-300M | 300g | 0.05g | 6,000e | Φ 120mm | 2.9kg | CE, OIML |
| NHB-600M | 600g | 0.1g | 6,000e | Φ 120mm | 2.9kg | CE, OIML |
| NHB-1500M | 1500g | 0.2g | 6,000e | 140 x 150mm | 2.7kg | CE, OIML |
| NHB-3000M | 3000g | 0.5g | 6,000e | 140 x 150mm | 2.7kg | CE, OIML |
| NHB-6000M | 6000g | 1g | 6,000e | 140 x 150mm | 2.7kg | CE, OIML |
| NHB+-150 | 150g | 0.001g | 150,000d | Φ 80mm | 2.9kg | CE |
| NHB+-1500 | 1500g | 0.01g | 150,000d | Φ 120mm | 2.9kg | CE |
| NHB++-200 | 200g | 0.001g | 200,000d | Φ 80mm | 2.9kg | CE |
| NHB++-2000 | 2000g | 0.01g | 200,000d | Φ 120mm | 2.9kg | CE |

Options



Print formats



Dimensions(mm)

