

S29 Waterproof Scales

General Specifications

- | | |
|------------------|--|
| • Display | 25mm digit LCD display, with white LED backlight |
| • Capacities | 3kg~25kg |
| • Platform size | 230 x 190mm |
| • Keyboard | 3keys (Mechanical switch) |
| • Housing | SST |
| • Max. Divisions | 3,000e; 2x3,000e; 6,000d |
| • ADC update | ≤1/10 second |
| • Operate Temp | -10°C~+40°C |
| • Power | AC adapter (12V/500mA), internal rechargeable battery (6V/3.2Ah) |
| • Gross weight | 4.2kg |



- China patented IP65 waterproof technology
- Selectable weighing units
- With hand breathable knob design
- OIML approval from Delta (approval no. DK0199.255)
- Battery provide up to 70 hours of continuous use (without backlight)
- Optional 20mm rear display
- Optional initial-verification



S29 Waterproof Scales

Model Name	Capacity	Readability	Division	Approx. weight	Approval
S29-3K	3kg	0.5g	6,000d	4.2kg	CE
S29-6K	6kg	1g	6,000d	4.2kg	CE
S29-15K	15kg	2g	6,000d	4.2kg	CE
S29-25K	25kg	5g	6,000d	4.2kg	CE
S29-3K-M	3kg	1g	3,000e	4.2kg	CE, OIML
S29-6K-M	6kg	2g	3,000e	4.2kg	CE, OIML
S29-15K-M	15kg	5g	3,000e	4.2kg	CE, OIML
S29-25K-M	25kg	10g	3,000e	4.2kg	CE, OIML
S29-6K-MR	6kg	1g/2g	2x3,000e	4.2kg	CE, OIML
S29-15K-MR	15kg	2g/5g	2x3,000e	4.2kg	CE, OIML
S29-25K-MR	25kg	5g/10g	2x3,000e	4.2kg	CE, OIML

Options



Dimensions(mm)

