

SW Waterproof Weighing Scales

General Specifications

- Display 25mm digit LCD display, with white LED backlight
- Capacities 3kg~30kg
- Platform size 200 x 260mm
- Keyboard 3 keys (Mechanical switch)
- Housing ABS plastic
- Max. Divisions 3,000e; 2 x 3,000e; 6,000d
- ADC update $\leq 1/10$ second
- Operating Temp. $-10^{\circ}\text{C} \sim +40^{\circ}\text{C}$
- Power AC adapter (12V/500mA), internal rechargeable battery (6V/3.2Ah)
- Gross weight 2.78kg



- IP65 waterproof housing design
- Selectable weighing units
- Hand operated pressure equalisation valve
- OIML approval from DELTA (approval no.DK0199.255)
- Battery provides up to 70 hours of continuous use (without backlight)
- Optional 15mm rear display
- Optional initial-verification



SW Waterproof Weighing Scales

Model Name	Capacity	Readability	Division	Approx. weight	Approval
SW-3K	3kg	0.5g	6,000d	2.78kg	CE
SW-6K	6kg	1g	6,000d	2.78kg	CE
SW-15K	15kg	2g	6,000d	2.78kg	CE
SW-30K	30kg	5g	6,000d	2.78kg	CE
SW-3K-M	3kg	1g	3,000e	2.78kg	CE, OIML
SW-6K-M	6kg	2g	3,000e	2.78kg	CE, OIML
SW-15K-M	15kg	5g	3,000e	2.78kg	CE, OIML
SW-30K-M	30kg	10g	3,000e	2.78kg	CE, OIML
SW-6K-MR	6kg	1g/2g	2 x 3,000e	2.78kg	CE, OIML
SW-15K-MR	15kg	2g/5g	2 x 3,000e	2.78kg	CE, OIML
SW-30K-MR	30kg	5g/10g	2 x 3,000e	2.78kg	CE, OIML

Options



Dimensions(mm)

